

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

Vivasil 501 Nano Sealer



Vivasil 501 Nano Sealer is a waterbase Nano Technology self organizing crosslink adhesion components gives the surface layered with hydrophobic properties. Vivasil 501 Sealer can be used on direct metal, wood, concrete, plastered surface and porous absorbent material. Vivasil 501 Sealer is a high performance for use with Vivasil Nano Touch Paint system. Its improves long term performance and durability. Vivasil 501 Sealer adds the strength and durability that can withstand from harsh climates. Design for use as undercoat or base coat for Vivasil Nano Touch Paint systems. Stir before use. Place in cool & dry. Close tight after use. Available in 5 and 18 litres.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

Undercoat-Vivasil Nano 501 Coat Sealer -Vivasil Nano Coat
Intermediate coat -Vivasil Nano Coat
Finish coat -Vivasil Nano Coat
Clear Coat-Vivasil UV Coat

Drying Time (@ 77 F, 50% RH):

When surface preparation is complete and surface is dry and free of dust, shake the container of Vivasil Nano Coat thoroughly as the nanoparticles will sink to the bottom. These need to be resuspended in order for proper performance of the coating.

Cracks, Chips Voids and Damages should be repaired. good flow out of application marks (e.g. brush-marking) forming a continuous protective film. quick drying

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery

* If you have any paint related questions please call our customer careline at **03-8737 2495**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor. Tel ; 603-87372495 Malaysia

Email address : enquiry@vivasil.com Website : www.vivasil.com

Facebook: www.facebook.com/vivasilpaints

