Technical Data Sheet

VIVASIL™
PROVEN PAINT TECHNOLOGY

GERMAN TECHNOLOGY

Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook: www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube: https://youtu.be/E3UaautZ5X4

Vivasil Bonding Agent Latex





Vivasil Bonding Agent Latex is specially designed latex admixture for tile adhesive. Recommended to mix with any tile adhesive cements, for walls & floors or thin set mortar applications, for high shear bond strength and submerged applications for tile on tile laying applications.

Vivasil Bonding Agent Latex is an admixture to be mixed with cement to form tiles bonding adhesive. Vivasil Bonding Agent Latex is fast setting adhesive for vertical and horizontal surfaces where obtaining high performance surfaces.

Vivasil Bonding Agent Latex is suitable for ceramic tiles, stone material, insulation panels ,gypsum boards and many other surfaces.

Vivasil Bonding Agent Latex should mix with neat portland cement as a slurry bond coat to fix rendered improves water resistance bonding agent and mortar-strengthening additive, ready to use material. & acts as bonding agent prior to fixing tiles.

Also aid in bonding prior to application of self-levelling compounds.Stir before use. Place in cool & dry. Close tight after use. Available in 5 and 20 litres.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

Cracks, Chips Voids and Damages should be repaired.good flow out of application marks (e.g. brush marking) forming a continuous protective film. quick drying. corrosion resistance. water resistance.

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer careline at ***03-8737 2495***

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)
38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000,
Kajang, Selangor.Tel ; 603-87372495 Malaysia
Email address : enquiry@vivasil.com Website : www.vivasil.com
Facebook: www.facebook.com/vivasilpaints