

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints , construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

Vivasil E-Coat WB-312



Vivasil E-Coat WB-312 Acrylic Sports floor coat is one component waterbase for tennis courts, public access ramps and steps, decks, patios ,flooring ,concrete, pavers, bituminous surface and sporting facilities paint.

Vivasil WB-312 is a water based non slip coating that is ideal for domestic and commercial applications.

Vivasil WB-312 is a multiple colour surface treatment. It is based upon the application of successive textured and finishing coats. When applied over asphalt and concrete surfaces it provides an all weather surface. Utilising 100% acrylic and high quality resins, flexibility is inherent to all our system.

The surface is hard wearing, long lasting with deep saturated colours. Even in wet conditions you will feel & play confidently with grip underfoot. Once fully cured,

Vivasil WB-312 coatings have a tough, rubberised, textured finish.Low sheen, non abrasive and durable, Vivasil WB-312 has excellent weathering properties making it ideal for outdoor application.It offers a quick drying, slip and abrasion resistant formula and easy water cleanup. Also a excellent high adhesion bonding technology and allowing shock and abrasion resistance for new and existing surfaces.

Non toxic, dust free, non flammable and abrasion resistance .

Vivasil E-Coat WB-312 Acrylic floor coat must properly primed with Vivasil WB-311 Primer before application .Stir before use. in 5 and 18 litres standard colour cards.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

Cracks, Chips Voids and Damages should be repaired.good flow out of application marks (e.g. brush marking) forming a continuous protective film.high opacity. quick drying. water resistance.

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer careline at **03-8737 2495**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor.Tel ; 603-87372495 Malaysia

Email address : enquiry@vivasil.com Website : www.vivasil.com

Facebook: www.facebook.com/vivasilpaints

