

# Technical Data Sheet



## Company Overview

Vivasil Paints ( M ) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: [enquiry@vivasil.com](mailto:enquiry@vivasil.com)

Facebook:  
[www.facebook.com/vivasilpaints](http://www.facebook.com/vivasilpaints)

Website: [www.vivasil.com](http://www.vivasil.com)

Youtube:  
<https://youtu.be/E3UaautZ5X4>

## Vivasil Epoxy Coating



Vivasil Epoxy Coating is a two component product supplied in 18 litre kits part A & B which contain the proper ratio of ingredients. The entire contents of each container must be mixed together.

After mixing the base portion, add the epoxy hardener part B slowly with part A continued agitation. After the hardener Part B add is complete, continue to mix slowly until homogeneous.

The pot life of the mixed material is 45 minutes at 25 C. Higher temperatures will reduce the working life of the coating - lower temperatures will increase it. Surface must properly primed with Vivasil Epoxy Primer before application. Stir before use. Place in cool & dry. Close tight after use. Available in 5 and 18 litres two pack system standard colour cards.

### PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

Undercoat-Vivasil Epoxy Primer

Intermediate coat -Vivasil Epoxy Coating

Finish coat -Vivasil Epoxy Coating

When surface preparation is complete and surface is dry and free of dust, shake the container of thoroughly as the particles will sink to the bottom. These need to be resuspended in order for proper performance of the coating.

Cracks, Chips Voids and Damages should be repaired. good flow out of application marks (e.g. brush-marking) forming a continuous protective film. quick drying

### Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

\* If you have any paint related questions please call our customer careline at **03-8737 2495**

**VIVASIL PAINTS (M) SDN. BHD.** (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor. Tel ; 603-87372495 Malaysia

Email address : [enquiry@vivasil.com](mailto:enquiry@vivasil.com) Website : [www.vivasil.com](http://www.vivasil.com)

Facebook: [www.facebook.com/vivasilpaints](http://www.facebook.com/vivasilpaints)

