

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

Vivasil Nano Matt Paint



Vivasil Nano Matt Paint is a waterbase Nano Technology self organizing crosslink adhesion components gives the surface layered with hydrophobic properties. Vivasil Nano Matt paint can be used on direct metal, wood, concrete, plastered surface and porous absorbent material. Surface must properly primed with Vivasil Nano Touch Sealer before application. Stir before use. Place in cool & dry. Close tight after use. Available in 5 and 18 litres.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

By spray, roller or brush

Inspect the surface before painting and all hairline cracks to be patched use Vivasil Patching Compound before application.

Undercoat-Vivasil Nano 501 Coat Sealer -Vivasil Nano Coat
Intermediate coat -Vivasil Nano Matt
Finish coat -Vivasil Nano Matt
Clear Coat-Vivasil UV Coat

Drying Time (@ 77 F, 50% RH):

When surface preparation is complete and surface is dry and free of dust, shake the container of Vivasil Nano Coat thoroughly as the nanoparticles will sink to the bottom. These need to be resuspended in order for proper performance of the coating.

Cracks, Chips Voids and Damages should be repaired. good flow out of application marks (e.g. brush marking) forming a continuous protective film. quick drying

Store in closed containers at temperature below 32°C and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer care line at **03-8737 2495**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor. Tel ; 603-87372495 Malaysia

Email address : enquiry@vivasil.com Website : www.vivasil.com

Facebook: www.facebook.com/vivasilpaints

