Technical Data Sheet

VIVASIL™
PROVEN PAINT TECHNOLOGY

GERMAN TECHNOLOGY

Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook: www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube: https://youtu.be/E3UaautZ5X4

Vivasil Waterproof Coating





Vivasil Waterproof Coating (Silicone Technologies) protects walls against carbonation & corrosion its highly elastic and waterproof suitable for bridging of cracks and easy to apply by brush, roller and spray. Interior and exterior use.

Not suitable for horizontal surfaces. Allows walls and render to breath ,Repairs & Permanently Prevents Cracking .
A solution to all your paint requirements .

Surface must properly primed with Vivasil Waterproof Coating Primer before application .Stir before use. Place in cool & dry. Close tight after use. Available in 18 litres standard colour cards.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc.

Undercoat-Vivasil Waterproof Sealer

Intermediate coat -Vivasil Waterproof Coating

Finish coat -Vivasil Waterproof Coating

When surface preparation is complete and surface is dry and free of dust, shake the container of thoroughly as the particles will sink to the bottom. These need to be resuspended in order for proper performance of the coating.

Cracks, Chips Voids and Damages should be repaired.good flow out of application marks (e.g. brush marking) forming a continuous protective film. quick drying

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer careline at ***03-8737 2495***

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)
38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000,
Kajang, Selangor.Tel ; 603-87372495 Malaysia
Email address : enquiry@vivasil.com Website : www.vivasil.com
Facebook: www.facebook.com/vivasilpaints