

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

Vivasil Alpha Seal Clear-Wet Areas Waterproofing



Vivasil Alpha Seal Clear is waterbase Polyurethane Modified waterproof repairing sealant ,its cures to and film forming to a flexible,transparent and tough membrane. High adhesion and high tensile strength.

Vivasil Alpha Seal Clear is for the customers who were experiencing leaky shower and balcony issues and didnt want to remove tiles as they were still in good condition apply Vivasil Alpha Seal Clear in leaking showers and balconies Just prepare and clean the area ,allow surface to dry,apply Vivasil Alpha Seal Clear and you,re done.

Vivasil Alpha Seal is a transparent stop leaks water based, non toxic environmental friendly elastomeric waterproof coating.which is tough, highly elastic for waterproof on horizontal and vertical cement surfaces, over concrete,toilets wall and floor joints,fish pond,water feature,floor trap leaking,crack repair>window aluminium sealing,block, brick, planter boxes,balconies,parapet walls,gutters,basement wall leaking and moisture blocking. Alpha seal is.highly water ponding resistance,mould resistance and work in wet surfaces which are able to stop leaking by brush coating.Surface must be clean and dry upon application.Avoid excessively thickness.

Recommended use roller or brush layer by layer

Dont apply too thick it can act as spot curing and create a hollow layer and cause pin holes. First layer to dry almost 4 to five hours,let it dry and cure before apply the second coat and the third coat.Do not apply in wet conditions or within 24 hours of rain. Apply to a dry surface, free of dirt, loose flaky paint and coatings, oil, grease, silicone, coal tar or other contaminants.

Topcoat- Vivasil Alpha Seal -3 to 4 coats

Application-Brush, roller or spray

Ready to use dilution not required

Touch Dry 80 Minutes

Fully cure 1 to 3 days

Theoretical Coverage 1.5kg per m² per

Stir before use. Place in cool & dry. Close tight after use.

Available in 5Litre and 18 Litre

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer careline at **03-8737 2495**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor.Tel ; 603-87372495 Malaysia

Email address : enquiry@vivasil.com Website : www.vivasil.com

Facebook: www.facebook.com/vivasilpaints

