Technical Data Sheet

VIVASIL™
PROVEN PAINT TECHNOLOGY

GERMAN TECHNOLOGY

Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook: www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube: https://youtu.be/E3UaautZ5X4

VIVASIL CLEAR SEAL-ROOF GLUE- UV RESISTANCE





Vivasil Clear Seal Roof Glue is non hacking water based elastomeric crack repair/roof coating highly UV resistance suitable for horizontal and vertical cement surfaces,over concrete,block, brick, cement render , fibrous cement ,planter boxes,roof, earth containing structures Not suitable for ponding water.

Exposed areas application only. Vivasil Clear Seal Roof Glue is high solid product modified acrylic rubber with nano technology of silicone polymer combine with modified silane creates high elongation and tensile strength.

Vivasil Clear Seal Roof Glue is also can be use as clear coating on existing roof coating and to be use to repair cracks on existing roof or aluminium windows and RC ledge surfaces which cause water leaks.
Highly UV resistance for indoor or outdoor application .Vivasil Clear Seal Roof Glue as a first coat layer and wait for 1 hour to dry for exterior surfaces, for interior surfaces let 2 to 4 hour to dry.

Dont apply too thick it can act as spot curing and create a hollow layer and cause pin holes. First layer to dry almost 4 to five hours,let it dry and cure before apply the second coat and the third coat.Do not apply in wet conditions or within 24 hours of rain. Apply to a dry surface, free of dirt, loose flaky paint and coatings, oil, grease, silicone, coal tar or other contaminants.

Topcoat- Vivasil Clear Seal Roof Glue -3 to 4 coats
Application-Brush, roller or spray
Ready to use dilution not required
Touch Dry 80 Minutes
Fully cure1 to 3 days
Theoretical Coverage1.5kg per m² per
Stir before use. Place in cool & dry. Close tight after use.
Available in 5Litre and 18 Litre

Storage:

Store in closed containers at temperature below 32oC and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer careline at ***03-8737 2495***

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)
38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000,
Kajang, Selangor.Tel ; 603-87372495 Malaysia
Email address : enquiry@vivasil.com Website : www.vivasil.com
Facebook: www.facebook.com/vivasilpaints