

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

VIVASIL NANO UV SEAL BLACK-OUTDOOR



Vivasil Nano UV Seal no hacking is a solvent free water based elastomeric crack repair/roof coating highly UV resistance suitable for horizontal and vertical cement surfaces, over concrete, block, brick, cement render, fibrous cement, planter boxes, roof, earth containing structures

Not suitable for ponding water. Exposed areas application only. Vivasil Nano UV Seal is high solid modified with polyurethane polymer emulsion creates high elongation and tensile strength.

Vivasil Nano UV-Seal is also elastomeric crack repair membrane which cause water leaks. Suitable for horizontal and vertical cement surfaces, over concrete, block, brick, cement render, fibrous cement, roof. Highly UV resistance for indoor or outdoor application.

Vivasil Flexo Sealer as a base coat layer and wait for 1 hour to dry for exterior surfaces, for interior surfaces let 2 to 4 hour to dry.

Don't apply too thick it can act as spot curing and create a hollow layer and cause pin holes. First layer to dry almost 4 to five hours, let it dry and cure before apply the second coat and the third coat.

Sealer / Primer- Vivasil Flexo Sealer
Topcoat- Nano UV Seal -3 to 4 coats
Application-Brush, roller or spray
Ready to use dilution not required
Touch Dry 80 Minutes
Fully cure 1 days
Theoretical Coverage 1.5kg per m² per
Stir before use. Place in cool & dry.
Close tight after use. Available in 1, 5 and 18 LITRE

Storage:

Store in closed containers at temperature below 32°C and away from heat sources and sunlight. When properly stored, will remain stable for 8 months from date of delivery.

* If you have any paint related questions please call our customer care line at **03-8737 2495**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

38A Jalan Sentosa 3, Taman Sentosa Sungai Jelok, 43000, Kajang, Selangor. Tel ; 603-87372495 Malaysia

Email address : enquiry@vivasil.com Website : www.vivasil.com

Facebook: www.facebook.com/vivasilpaints

