# Technical Data Sheet

VIVASIL™
PROVEN PAINT TECHNOLOGY

GERMAN TECHNOLOGY

## Company Overview

Vivasil Paints ( M ) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook: www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube: https://youtu.be/E3UaautZ5X4

# Vivasil 658 Epoxy Crack Grout






Vivasil 658 Epoxy Grout is a two component product supplied in kits part A,B & C which contain the proper ratio of ingredients. The entire contents of each container must be mixed together. After mixing the base portion, add the epoxy hardener part B,and C slowly with part A continued agitation. After the hardener Part B add is complete, continue to mix slowly until homogeneous.The pot life of the mixed material is 30 minutes at 25 C. Place in cool & dry. Close tight after use. Available in 8.5kg(5Litre) or 10 Litre(17Kg) set.

| | |
|---|---|
| Part A 4 litre | Part A 4.9 litre |
| Part B 1 Litre | Part B 2.2 litre |
| Part C 5 Kg | Part C 10 Kg |

**PREPARATION OF SURFACE**

Vivasil 658 Epoxy Grout bonds, levels, fills, rebuilds, and resurfaces concrete and most rigid surfaces.This versatile epoxy is blended with fine sand, creating a structural grout and filler that can be used for countless applications.Repair industrial floors, docks, sidewalks, driveways, stairs, parking decks, and more.Vivasil 658 Epoxy Grout is perfect for fixing pitted, spalled, worn, or cracked concrete and is ideal for salt damage repairs. It makes a great slip-resistant floor and deck coating by broadcasting sand or other aggregates over the wet . Vivasil 658 Epoxy Grout works great for anchoring posts and railings and installing machinery, precasts, columns, and more. Use with forms to rebuild steps and vertical columns.Vivasil 658 Epoxy Grout creates repairs that are permanent and cost-effective. It is easy to mix and apply. Blend in fine sand to create a cement-like epoxy compound that self-levels and is shrink-free. Thicken the compound by adding additional sand or aggregate. Vivasil 658 Epoxy Grout can be applied in any thickness for a finish that is stronger than concrete! It is unaffected by salt water, oils, and chemicals that erode concrete. It holds up well to heavy forklift and truck traffic.

Recommended
Theorial coverage : 0.5 to 0.8 m2 per litre
Base Epoxy Resin Solution
Colour Greenish Grey
Potlife @ 65% R.H 30 minutes
Drying Time 10C – 240 min
Full cure 3 days at 23oC
Overcoat Time 10C – 120 min
20C – 60 min
24 hours for all other coatings

* If you have any paint related questions please call our customer careline at ***06-790 9222***

**VIVASIL PAINTS (M) SDN. BHD.** (1117204-T)
167,Jalan Nilai 3/16, Kawasan Perindustrian Nilai 3,
71800, Nilai ,Negeri Sembilan,
Tel ; 606-790 9222 Malaysia
Email address : enquiry@vivasil.com Website : www.vivasil.com
Facebook: www.facebook.com/vivasilpaints