

Technical Data Sheet



Company Overview

Vivasil Paints (M) Sdn Bhd is a manufacturing and supplying paint coating products.

Our company has witnessed accelerated growth and development under the prudent management.

Our company produces the full range of architectural paints construction materials and industrial paints for local market and oversea markets.

Vivasil color products has widened to include specialist and designer products.

For more information:

Email: enquiry@vivasil.com

Facebook:
www.facebook.com/vivasilpaints

Website: www.vivasil.com

Youtube:
<https://youtu.be/E3UaautZ5X4>

Vivasil Weatherpro Acrylic paint



Vivasil Weatherpro 100% acrylic is toughest paint for all exterior surfaces. Formulated by with our exclusive anti fading, anti fungus, anti peeling Technology that brings a new level of hard wearing toughness to the exterior of your home. Weatherpro to perform in any climatic conditions. Vivasil Weatherpro should always be applied before one coat of Vivasil WB-301 Acrylic Sealer and to be continued with minimum of two finishing coats of Vivasil Weatherpro Finishes. All newly plastered walls should be allowed to dry completely or cure at least 21 days before painting works.

PREPARATION OF SURFACE

All the surface must be dry, clean and free from contaminants such as dust, dirt, moss/fungus, oil, grease and ridges etc. Cracks, Chips Voids and Damages should be repaired
Old acrylic paint must be scrapped, waterjet, removed & cleaned.

APPLICATION FOR NEW SURFACES

Apply 1 coat Vivasil WB-301 Acrylic Sealer
Allow to dry for 45 Minutes
Apply 2nd Coat of Vivasil Weatherpro

APPLICATION FOR EXISTING SURFACES

Apply 1 coat Vivasil WB-301 Acrylic Sealer
Allow to dry for 45 Minutes
Apply 2nd Coat of Vivasil Weatherpro

No water / rain should be allowed on Painted surface for 1 days after application
Theoretical coverage 7 - 10 m² per litre per coat
Touch dry 40 minutes
Full cure 3 days

* Store at cool and dry place in sealed containers. No water / rain should be allowed on Painted surface for 1 days after application

* If you have any paint related questions please call our customer careline at **06-790 9222**

VIVASIL PAINTS (M) SDN. BHD. (1117204-T)

167Jalan Nilai 3/16, Kawasan Perindustrian Nilai 3, 71800, Negeri Sembilan. Tel ; 606-790 9222 , 019-6432495 Malaysia
Email address : enquiry@vivasil.com Website : www.vivasil.com
Facebook: www.facebook.com/vivasilpaints

